

Listing of the Claims:

This listing of claims will replace all prior versions, and listings, of claims in the application.

1. (Currently Amended) A spa bath including at least one spa jet fitting having a front part which comprises a front face exposed to the interior of the bath cavity, the front part of the spa jet fitting having a diameter across the front face, the spa jet fitting being mounted within a recess formed in the wall of the spa bath facing into the interior of the spa bath and having a diameter across the recess substantially the same as the diameter of the front part of the spa jet fitting, the front face of the spa jet fitting being solid but for at least one outlet through the front face of the fitting, the front face of the fitting ~~which does not protrude~~ beyond ~~a~~ the surface of the bath wall immediately around the front part of the spa jet fitting.

2. (Previously Presented) A spa bath according to claim 1 wherein at least a major portion of the front face of the spa jet fitting is substantially flush with the surface of the bath wall around the spa jet fitting.

3. (Previously Presented) A spa bath according to claim 1 wherein the spa jet fitting is a water jet outlet fitting and wherein the front face of the spa jet fitting comprises a ring which is rotatable to adjust water or air flow from the spa jet fitting.

4-5. (Cancelled).

6. (Currently Amended) A spa bath including at least one spa jet fitting mounted through an aperture through a wall of the spa bath and in a mounting recess formed in the wall of the spa bath around said aperture, said mounting recess having facing into the interior of the spa bath and comprising inwardly angled side walls comprising part of the wall of the spa bath, the spa jet

fitting comprising a front part which is exposed to the interior of the bath and which includes an edge portion about the periphery of the front part which is tapered with reducing diameter toward a rear part of the spa jet fitting, which tapered peripheral edge portion of the front part seats in the mounting recess in the side wall of the bath and against said inwardly angled side walls of the mounting recess to centers the spa jet fitting in the recess.

7. (Previously Presented) A spa bath according to claim 6 wherein said front part includes a front ring which provides the wide diameter front face of the spa jet fitting.

8. (Previously Presented) A spa bath according to claim 6 wherein the spa jet fitting is a water jet outlet fitting and wherein the front face of the spa jet fitting comprises a ring which is rotatable to adjust water or air flow from the spa jet fitting.

9-10. (Cancelled).

11. (Currently Amended) A spa bath fitting adapted for mounting in a through a wall of a spa bath, through an aperture through the wall of the bath and in a mounting recess formed in the wall of a bath around said aperture, said mounting recess facing into the interior of the spa bath and comprising having inwardly angled side walls, the spa bath fitting comprising a rear part or back nut having a leading edge ~~which contacts the rear surface of the recess in the bath wall, which leading edge~~ is tapered with a reducing diameter toward a rear part of the fitting to contact the rear surface of the inwardly angled side walls of the mounting recess in the bath wall to which assists in centering the spa bath fitting in the recess in the side wall of the bath.

12. (Previously Presented) A spa bath fitting according to claim 11 which comprises separate threadedly coupled front and rear parts and a separate back nut for fixing the spa bath fitting to the bath so as to enable the position of the front face of the spa bath fitting to be adjusted relative to the rear part separate from tightening of the back nut to fix the spa bath

fitting in place, enabling adjustment during installation of the spa_bath fitting of the position of the exposed front face of the spa bath fitting relative to the bath wall.

13. (Previously Presented) A spa bath fitting according to claim 12 wherein the fitting is a water jet outlet fitting and wherein the front face of the fitting comprises a ring which is rotatable to adjust the water or air flow from the spa bath fitting.

14. (Previously Presented) A spa bath fitting according to claim 12 wherein the front part includes a separate front ring which provides the wide diameter front face of the spa jet fitting.

15. (Previously Presented) A spa bath fitting according to claim 13 wherein the front face of the spa bath fitting includes one or more shallow recesses into which a users finger or fingers may fit to facilitate rotation of the to adjust water or air flow from the spa bath fitting.

16. (Previously Presented) A spa bath fitting according to claim 12 wherein the spa bath fitting is a water jet outlet fitting and includes a central eyeball nozzle which is movable to adjust the direction of water flow from the spa bath fitting.

17. (Currently Amended) A spa bath fitting including:- a front part including ring which provides a wide diameter front face which is exposed to the interior; of the bath at a front side of the side wall or base of the bath when the spa bath fitting is mounted in the a side wall or base of a bath, a front part separate from the front ring, and behind the front ring and to which the front ring connects and is mounted when the spa bath fitting is mounted in the side wall or base of a bath, a rear part which is positioned on the a rear side of the bath wall or base when the spa bath fitting is mounted in a bath and with which the front part is threadedly connected, and a back nut mounted on the rear part for fixing the spa bath fitting in the bath wall or base- the front part including a tail for passing through said aperture in the bath wall or base and which has a threaded end which threadedly connects with the rear part of the spa bath fitting, and the back

nut threadedly mounting on the exterior of the rear part of the spa bath fitting so that the back nut can be screwed up against the rear side of a bath wall or base so that the bath wall or base around said aperture in the bath wall or base is captured between the front part of the fitting and the back nut, to lock the spa bath fitting in place in the bath wall or base.

18. (Cancelled).

19. (Currently Amended) A spa bath fitting according to claim 18₁₇ wherein the tail of the front part of the spa bath fitting is externally threaded and the rear part comprises a complementary threaded bore into which the threaded tail of the forward part connects.

20. (Cancelled).

21. (Currently Amended) A spa bath fitting according to claim 20₁₇ wherein the front ring snap- fit connects to another section of the forward part of the spa bath fitting.

22. (Currently Amended) A spa bath fitting according to claim 20₁₇ wherein the front ring screw threadedly connects to another section of the forward part of the spa bath fitting.

23. (Previously Presented) A spa bath fitting according to claim 17 wherein a forward face of the back nut is tapered to assist in self- centering the spa bath fitting during the tightening of the back nut against the rear of the bath wall or base.

24. (Previously Presented) A spa bath fitting according to claim 17 wherein a peripheral edge portion of the forward part is tapered with reducing diameter toward the rear part of the spa bath fitting to assist in centering the spa bath fitting in a recess in the wall or base of a bath.

25. (Previously Presented) A spa bath according to claim 17 wherein the spa bath fitting is a water jet outlet fitting and wherein the front face of the spa bath fitting comprises a ring which is rotatable to adjust the water or air flow from the spa bath fitting.

26-27. (Cancelled).